



INTELLO® and INTELLO® PLUS are compatible with all pro clima adhesive tapes and sealants. Optimum long term durability on air tightness is achieved by good quality connections between INTELLO® range and other building materials and components. The table below provides guidance on the use of pro clima adhesive and sealing products when used to connect INTELLO® or INTELLO® PLUS with common building materials for durable airtight connections.

		TESCON® VANA	TESCON® PROFIL	TESCON EXTORA®	TESCON EXTORA® PROFIL	ORCON® CLASSIC	KAFLEX® IQ	KAFLEX mono/duo	ROFLEX	DUPLEX	TESCON® PRIMER RP	AEROSANA® VISCONN
Timber, OSB, Plywood	dirty									✓	✓	
	clean	✓	✓	✓	✓	✓				✓	✓	
Plaster board	clean	✓	✓	✓	✓	✓				✓	✓	
Paint primers		✓	✓	✓	✓	✓				✓	✓	✓
AEROSANA® VISCONN	dry / clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PIR Polysiocanurate	on foil	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	on PIR											
XPS Extruded Polystyrene	clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
EPS Expanded Polystyrene	clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Expanding foams	dry											✓
Cement / Gypsum plaster	smooth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough				✓						✓	✓
	friable										✓	✓
Acrylic plaster	smooth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough				✓						✓	✓
Steel	galvanised	✓	✓	✓	✓	✓				✓		
	bright	✓	✓	✓	✓	✓				✓		
	painted	✓	✓	✓	✓	✓				✓		
Aluminium	clean	✓	✓	✓	✓	✓				✓		
Brickwork	rough				✓						✓	✓
	friable										✓	✓
Concrete	smooth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough				✓						✓	✓
Fibre cement	clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	friable										✓	✓
Windows	aluminium	✓	✓	✓	✓	✓				✓		
	PVC	✓	✓	✓	✓	✓				✓		
	timber	✓	✓	✓	✓	✓				✓		
Cables*	flat	✓	✓	✓	✓	✓		✓				
	round	✓	✓	✓	✓	✓		✓				
Pipes / ducts*		✓	✓	✓	✓	✓		✓				

### Note

Surfaces should always be dry and free from dust and grease.

TESCON® PRIMER RP is always recommended for mineral based surfaces.

\* KAFLEX / ROFLEX should always be the first choice when sealing penetrations.



### Your local support

04 589 8460 | 09 892 9900 | 03 327 4925

Technical: support@proclima.co.nz | General: welcome@proclima.co.nz

www.proclima.co.nz

