

## Safety Data Sheet

### KERAQUICK S1 grey

Safety Data Sheet dated: 21/07/2021 - version 2

## Section 1. Identification of the substance and supplier

### Product identifier

Mixture identification:

Trade name: KERAQUICK S1 grey

Trade code: 9001252

### Recommended use of the chemical and restrictions on use

Recommended use: Cement based powder adhesive

Uses advised against: Data not available

### Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road - Mount Wellington - 1060 - Auckland - New Zealand

Phone: +64 9 921 1994 (Mon-Fri 9am-5pm) - Fax: +64 9 921 1993

enquiries@MBPLtd.co.nz - www.MBPLtd.co.nz

### Emergency phone number

New Zealand Poisons Centre: Ph: 0800 764 766

## Section 2. Hazards identification

### HSNO hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

### HSNO classification:

- 6.3B H316 - Causes mild skin irritation.  
6.4A H319 - Causes serious eye irritation.  
6.5B H317 - May cause an allergic skin reaction.

### Hazard information

#### Pictograms and Signal Words



Warning

### Hazard statements:

- H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

### Precautionary statements:

- P261 Avoid breathing dust.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see supplementary instructions on this label).  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P501 Dispose of contents/container in accordance with applicable regulations.

### Other hazards which do not result in a classification

No other hazards

Prolonged exposition and/or intensive inhalation of respirable free crystalline silica (average diameter less than 10 micron in accordance with ACGIH) can cause pulmonary fibrosis commonly referred to as silicosis.

## Section 3. Composition/information on ingredients

### Substances

N.A.

## Mixtures

Mixture identification: KERAQUICK S1 grey

### Hazardous components within the meaning of HSNO Act and related classification

| Concentration (% w/w) | Name                            | Ident. Numb.                   | Classification  |
|-----------------------|---------------------------------|--------------------------------|---|
| ≥1 - <2.5 %           | Portland cement, Cr(VI) < 2 ppm | CAS:65997-15-1<br>EC:266-043-4 | 6.3A, H315; 6.5B, H317; 8.3A, H318; 6.1E (respiratory tract irritant), H335 |

---

## Section 4. First aid measures

### Description of necessary first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

### Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

- (see paragraph 4.1)

### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

---

## Section 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO<sub>2</sub>).

Unsuitable extinguishing media:

- None in particular.

### Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: ==
- Oxidizing properties: N.A.

### Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

---

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.

### Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

### Methods and materials for containment and cleaning up

- Take up mechanically and dispose of according to local/state/federal regulations
- Scoop into containers and seal for disposal.
- Retain contaminated washing water and dispose it.

---

## Section 7. Handling and storage

### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

---

## Section 8. Exposure controls/personal protection

### Workplace Exposure Standards

#### List of components with OEL value

| Component                       | OEL Type | Country     | Ceiling | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Behaviour Note |
|---------------------------------|----------|-------------|---------|-----------------|---------------|------------------|----------------|----------------|
| Portland cement, Cr(VI) < 2 ppm | NZL      | NEW ZEALAND |         | 10.000          |               |                  |                |                |
|                                 | NZL      | NEW ZEALAND |         | 3               |               |                  |                |                |
|                                 | NZL      | NEW ZEALAND |         | 1               |               |                  |                |                |

### Engineering Controls

N.A.

### Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluorinated rubber - FKM: thickness  $\geq 0,4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

A dust mask (P2) should be worn if above exposure limits (EN 149)

Thermal Hazards:

N.A.

---

## Section 9. Physical and chemical properties

Physical state: Solid

Appearance and colour: powder white/grey

Odour: cement like

Odour threshold: N.A.

pH: N.A.

pH (water dispersion, 10%): 12.25

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: N.A.

Flammability (Solid, Gas): N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: N.A.

Vapour density: N.A.  
Relative density: N.A.  
Solubility in water: <5 g/l  
Solubility in oil: insoluble  
Partition coefficient (n-octanol/water): N.A.  
Auto-ignition temperature: N.A.  
Decomposition temperature: N.A.  
Kinematic viscosity: N.A.  
Particle characteristics: No data available

---

## **Section 10. Stability and reactivity**

### **Reactivity**

Stable under normal conditions

### **Chemical stability**

Data not available.

### **Possibility of hazardous reactions**

None.

### **Conditions to avoid**

Stable under normal conditions.

### **Incompatible materials**

None in particular.

### **Hazardous decomposition products**

---

## **Section 11. Toxicological information**

### **Information on toxicological effects**

---

## **Section 12. Ecological information**

### **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

### **Persistence and degradability**

N.A.

### **Bioaccumulative potential**

N.A.

### **Mobility in soil**

N.A.

### **Other adverse effects**

N.A.

---

## **Section 13. Disposal considerations**

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

### **Special precautions to be taken during disposal**

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

---

## Section 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

### UN number

N.A.

### UN proper shipping name

N.A.

### Transport hazard class(es)

N.A.

### Packing group, if applicable

N.A.

### Environmental hazards

N.A.

No

### Special precautions for user

NZS-Subsidiary risks: N.A.

NZS-Special Dispositions: N.A.

Road and Rail ( ADR-RID ) :

N.A.

ADR-Hazard identification number: NA

Air ( IATA ) :

N.A.

Sea ( IMDG ) :

N.A.

---

## Section 15. Regulatory information

### HSNO Approval

HSNO approval number and group standard title:

HSR002544 - Construction Products (Subsidiary Hazard) Group Standard 2006

### HSNO Controls

#### Approved Handler

No data available

### New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

### Regulatory references

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Hazardous Substances (Classification) Regulations 2001.

Labelling of Hazardous Substances: Hazard and Precautionary Information (January 2012 EPA0094).

Assigning a Product to a HSNO Approval (May 2013/Revised June 2014).

---

## Section 16. Other information

Safety Data Sheet dated: 21/07/2021 - version 2

| Code | Description                          |
|------|--------------------------------------|
| H315 | Causes skin irritation.              |
| H316 | Causes mild skin irritation.         |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage.           |
| H319 | Causes serious eye irritation.       |
| H335 | May cause respiratory irritation.    |

### Description of the HSNO Classification codes used in section 2 or 3:

| Code                              | Description  |
|-----------------------------------|--|
| 6.1E (respiratory tract irritant) | Respiratory tract irritant.                        |
| 6.3A                              | Substances that are irritating to the skin.        |
| 6.3B                              | Substances that are mildly irritating to the skin. |
| 6.4A                              | Substances that are irritating to the eye.         |
| 6.5B                              | Substances that are contact sensitisers.           |

8.3A Substances that are corrosive to ocular tissue.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

HSNO: Hazardous Substances and New Organisms Act 1996.

**Paragraphs modified from the previous revision:**

- 2. HAZARDS IDENTIFICATION
- 6. ACCIDENTAL RELEASE MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION