

SUPER-STICK



Tape sizes:

- 75mm x 23m
- 150mm x 23m
- 200mm x 23m



A GREENER SOLUTION

- No VOCs, HFCCs or CFCs
- Non-allergenic
- No off-gassing
- No toxicity



Marshall Innovations SUPER-STICK Building Tape® is a high performance window and door flashing tape designed to be installed down to $-6 \text{ deg}^{\circ}\text{C}$. No more issues regarding adhesion in the cool of winter or heat of summer. No additional primers or mechanical fasteners required. SUPER-STICK Building Tape® utilizes a high tack pressure

sensitive adhesive (PSA) combined with a high performance toughened film. It is a greener and cleaner building tape solution that contains No VOC's, HFCC's, nor CFC's. It is non-toxic and non-allergenic. No more issues with sealant compatibility at the design or installation stage.

BENEFITS

- Can be installed in extremely cold conditions to $-6 \text{ deg}^{\circ}\text{C}$ *
- Easy to install peel-and-stick application
- UV resistant for 90 days
- Compatible with most sealants, check suitability with sealant manufacturer
- Can be used with RAB systems - Plywood, fibre cement sheet
- Split back liner for easy install
- Can be installed in very hot conditions
- Extremely high puncture resistance and tensile strength

- Residential and Commercial applications
- Very thin and no build up and won't affect cavity battens or window installation
- BRANZ SUPER-STICK #846 (2019)
- CodeMark CM70015 (2019)
- Forms part of the Marshall Weatherization System

Note: Protecto SUPER-STICK Tape® can be applied in extreme cold weather; however we do not recommend applying tapes below 0°C due to health and safety reasons. *When applying over any waterproofing membrane check for compatibility.

