



## Technical data

Substance		
Material	polyethylene, flexible and extensible	
Attribute	Regulation	Value
Colour		white
Length / width installation space/cavern		260 mm / 130 mm
Length / width over all		320 mm / 190 mm
Depth		55 mm
Cable diameter		max. 20 mm
MVTR		> 50 MNs/g
Reaction to fire	DIN EN 13501-1	E
Temperature resistance		permanent -10 °C to +80 °C
Storage		cool and dry

## Area of application

For structures without dry lining, the INSTAABOX can create space for junction boxes and the like. It is attached and sealed so that it is airtight to the existing vapour retarding and airtightness layer.

It complies with the requirements of DIN 4108-7, SIA 180 and OENORM B 8110-2 with regard to airtightness when using conventional junction boxes. The INSTAABOX can be used for both internal and external walls.

The INSTAABOX is oversized to prevent the airtight sealing layer being damaged if holes need to be drilled for the junction boxes.

## Forms of delivery

Art. no.	GTIN	Length	Width	Contents	Weight
11751	4026639117519	320 mm	190 mm	5 pieces	0.13 kg
11942	4026639119421	320 mm	190 mm	20 pieces	0.52 kg
12181	4026639121813	0	0	5 pieces	0.13 kg
13601	4026639136015	0	0	20 boxes	0.52 kg

## Advantages

- ✓ Airtight installation of junction boxes without dry lining in accordance with the requirements of DIN 4108-7, SIA 180 and OENORM B8110-2
- ✓ Provides space for up to three junction boxes
- ✓ Can be extended at will by cutting and sticking together again
- ✓ For cables up to 20 mm in diameter

## Substrates

The INSTAABOX can be used on all common airtight substrates used in construction. Recommendations on suitable sealants for connecting it to the airtight sealing layer (e.g. vapour retarder, wood-based panels or mineral substrate) is given in the pro clima application matrix.

Further information can be found in the technical data sheets provided with the sealant.

## General conditions

The bonds should not be subjected to tensile strain.

When the vapour control membrane is sealed, the weight of the insulating material must be borne by lathing. The adhesive tape should be supported by battens if necessary.

Press firmly to secure the adhesive tape. Ensure there is sufficient back-pressure.

Airtight seals can only be achieved on vapour control membranes that have been laid without folds or creases.

Ventilate regularly to prevent build-up of excessive humidity and use a dryer if necessary.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

### MOLL

#### bauökologische Produkte GmbH

Rheinalstraße 35 - 43

D-68723 Schwetzingen

Fon: +49 (0) 62 02 - 27 82.0

Fax: +49 (0) 62 02 - 27 82.21

eMail: info@proclima.de





\* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

**Made in Germany**  
developed and produced by  


The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

**MOLL**  
**bauökologische Produkte GmbH**  
Rheintalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
Fax: +49 (0) 62 02 - 27 82.21  
eMail: [info@proclima.de](mailto:info@proclima.de)

