

Hydro™ Seal

Bituminous Masonry Sealer



Hydro Seal is a black waterproof membrane that has been formulated to act as a barrier behind retaining walls and buried structures.

Applications

- Suitable for concrete, concrete block and brick-work, wood and metal.
- Hydro Seal is simple to apply by brush or roller
- Is compatible with green concrete
- Has excellent adhesion to masonry and concrete etc.
- Fast cure time
- Low water permeability
- Sulphates and ground salts resistant

New Zealand Building Code Standard (NZBC)

- Passed the vapour flow resistance level requirements for a water vapour barrier as per E2/AS1
BRANZ Rapport number DC2547
- Meets moisture vapour permeability requirements of NZS 3604:2011

Physical Properties

| | |
|--------------------------|--|
| Form: | Thyrotropic liquid mixed |
| Solid content: | 60% |
| Density: | 1.00kg/L |
| Application temperature: | 5°C to 50°C |
| Drying Time: | 4 - 6 hours at 20°C, 12 - 24 hours should be left between coatings |
| Coverage: | Additional to the primer coat - The minimum total application rate is 1 Liter per m ² (2 coats of 1/2 litre per m ² each). Depending on the substrate quantities this might vary slightly. |
| Limitations: | Not to be exposed to sunlight. Not to be over-coated with paint |
| Shelf live: | 12 months when stored in original packaging. Store between 1°C - 35°C |

TIP: Protect Hydro™ Seal with Masons FOAM GUARD

Hydro™ Seal membrane can be subject to punctures and abrasion due to coarse backfill. By simply applying the self adhesive foam guard you significantly reduce the risk of this happening.



| Masons Hydro™ Seal | Bucket Size | Masons Code |
|--|-------------|--------------|
| Hydro Bituminous Surface Treatment 4L | 4 Litre | HYDROSEAL4L |
| Hydro Bituminous Surface Treatment 20L | 20 Litre | HYDROSEAL20L |