

# Barricade FR

## Fire Retardant Building Wrap

Barricade FR is a fire retardant building wrap suitable for all frame and cladding systems with or without cavity. It is Codemark Certified.



FIRE RETARDANT



RESISTS UV EXPOSURE FOR UP TO 60 DAYS



CUSTOM BRANDING AVAILABLE



**MASONS**  
Designed Smart, Built Tough.

### QUALITY BUILDING WRAP

A non-woven fire retardant, water resistant, breathable synthetic wall underlay for use under direct fixed and non-direct fixed wall cladding on timber framed and steel framed buildings.

### ANTI FUNGAL PROPERTIES


Barricade FR has unique anti-fungal properties.

### RESISTS UV EXPOSURE

Manufactured from high quality synthetic spun bonded material with high UV qualities to resist UV exposure for up to 60 days.

### APPLICATIONS

- To be used where a fire retardant wrap is required. It performs well with all cladding systems and over timber or steel framing.
- Barricade FR is absorbent and can be used with absorbent and non-absorbent cladding.
- Strong and durable. Suitable for all areas of New Zealand including up to 'Very High' wind zones of NZS 3604 and "Extra High" over rigid wall underlays.
- Suitable as a non rigid backing for stucco plaster.
- Suitable as an air barrier on walls that are not lined.
- Can be used on gable ends.
- Vertical use only. Not suitable as a roof underlay.



**CodeMark** >>>

CMNZ70072



**MASONS**  
Designed Smart, Built Tough.

## NEW ZEALAND BUILDING CODE STANDARD (NZBC)

The following tests have been carried out in accordance with NZBC Acceptable Solution E2/AS1 Table 23:

Tensile strength, edge tear resistance and resistance to water vapour transmission in accordance with AS/NZS 4200.1	Pass
Resistance to water penetration in accordance with AS/NZS 4201.1.4	Pass
Surface water absorbency in accordance with AS/NZS 4201.6	Pass
Air resistance to BS 6538.3	Pass
Shrinkage in accordance with AS/NZS 4201.3	Pass
pH of extract in accordance with AS/NZS 1301.421	Pass
Fire retardant in accordance with AS1530 Part 2 Flammability	Pass

Available as: 2.74m, 1.37m and 0.6m widths and multiple linear lengths.

Description	Masons Code	Size of Roll
Barricade FR Building Wrap 2.74m x 50m <sup>2</sup>	BFRMPB2.74x50	2.74m x 50m <sup>2</sup>
Barricade FR Building Wrap 2.74m x 100m <sup>2</sup>	BFRMPB2.74x100	2.74m x 100m <sup>2</sup>
Barricade FR Building Wrap 1.37m x 100m <sup>2</sup>	BFRMPB1.37x100	1.37m x 100m <sup>2</sup>
Barricade FR Building Wrap 1.37m x 50m <sup>2</sup>	BFRMPB1.37x50	1.37m x 50m <sup>2</sup>
Barricade FR Building Wrap 1.37m x 25m <sup>2</sup>	BFRMPB1.37x25	1.37m x 25m <sup>2</sup>
Barricade FR Wrap 0.6m x 21.9m <sup>2</sup>	BFRMPB0.6x22	0.6m x 21.9m <sup>2</sup>
<b>Custom Branded Barricade FR</b>		
BFR Building Wrap 2.74m x 100m <sup>2</sup>	tbc on order	2.74m x 100m <sup>2</sup>

### CUSTOM BRANDED WRAP

Barricade FR is available custom branded with your logo. Printed in black or one specified PMS colour. A perfect way to give your company brand exposure.

**Custom Branded BFR is available by the pallet**

**Number of rolls to a pallet: 64**

**Minimum order:**

Conditions apply.  
See your Masons representative.

**Rows of client logos: 3** (2.74m roll)

**Lead time: 16 weeks.**

Conditions apply.  
See your Masons representative.

All orders are shipped on arrival.  
No stock is held by Masons.

Logos to be supplied by the client.  
A guide to supplying logos for BFR is available from your Masons representative.

Design repeating every 1.2m

